

601/601M Incl Tronic plus



Horizontal and vertical vial – can also be used as a regular level. Measuring accuracy 0.5 mm/m.

Measuring accuracy for both vials in normal and inverted position: 0.5 mm/m

Electronic inclinometer
Accuracy at 0° and 90° $\pm 0.05^\circ$
Accuracy at 1° to 89° $\pm 0.2^\circ$
Battery: E-block 9 Volt 6LR61.
Extra long operating time

Sturdy powder-coated aluminum 4 chamber profile with 2 milled measuring surfaces



Display with backlight

Incli Tronic measures angles electronically and displays them digitally. The measuring processor can be calibrated both horizontally and vertically within seconds.

- Measures angles in degree, percentage, mm/m and inch/ft at the touch of a button
- Measurements displayed in the following steps: 0.05, 0.01°/IN/FT, 0.1°, 0.1% or in 1.0 mm/m
- Arrows in the display indicate the direction the Incl Tronic needs to be moved to reach 0° or 90°
- By pressing the "Hold" button, the current measurement can be saved
- Intermediate angles can be set as reference points
- Two different beeps when approaching level/plumb position from left or Right
- Automatically powers off after 6 minutes
- **Delivery:** in sturdy translucent plastic tube. Batteries included.

Length in cm	60	80	120	180	200
Article N°.	601 060	601 080	601 120	601 180	601 200
Article N°.	601 060 M	601 080 M	601 120 M	601 180 M	601 200 M



measurement display in degrees or %



measurement display in mm or inch/feet

