

## 411 VARIO EC I High Precision

The latest production process ensures the most precise measurements. All other features are the same as the Vario Standard. Allowed tolerance:

### Comparison

	EG I	to	EG II
1 m	± 0,3 mm		± 0.7 mm
2 m	± 0,4 mm		± 0.9 mm
3 m	± 0,5 mm		± 1.1 mm
5 m	± 0,7 mm		± 1.5 mm
8 m	± 1,0 mm		± 2.1 mm



made in  
Germany  
BMI

Length	2 m	3 m	5 m	8 m
Graduation	mm	mm	mm	mm
Width	13 mm	13 mm	16 mm	19 mm
Article N°.	411 2418	411 3418	411 5418	411 8418

**exclusive  
advantages  
provided only  
by BMI!**



### Hook-Airbag

The hook rest area is more spacious to protect the stainless steel hook from damage and deformation upon impact.



### Effortless locking

Especially handy is the easy to press blade locking button. A light press of the finger is all that is necessary to lock the blade in place.



### Lightweight

25 % less volume; 5 % less weight. The ideal pocket tape for professional use.



### Kickback-free

The rubber T-formed damper absorbs the blade kickback energy. It makes the recoil of especially long tapes more comfortable on the hand and wrist.



### Remarkably smooth

The hub and tape release are made of TRIBOCOMP® with Teflon. This special material ensures a super smooth blade function and an exceptionally effortless tape return.



### Sleek belt clip

The belt clip\* is made of smooth stainless steel wire without any sharp edges – allowing quick and easy attachment and removal without damaging your belt.



### Scratch me if you can!

A special clear varnish protects the blade from wear. An additional anti-glare coating makes the tape easy to read under all lighting conditions.

\*optional with surcharge

made in  
Germany  
BMI