

## Digitales Dicken-Messgerät, Ablesung 0,01 mm oder 0,0005"

565/3

Digital thickness gauge, reading 0.01 mm or 0.0005"



- Taster aus rostfreiem Stahl
- Bügel aus Gusseisen, lackiert
- Feder schließend
- Ablesung 0,01 mm oder 0,0005"
- im Etui

- rod and disc made of stainless steel
- frame made of case iron
- spring closed
- reading 0.01 mm or 0.0005"
- in case

ON / OFF	●
mm / inch (Unit)	●
HOLD-Funktion	
ABS-Funktion	
Absolut-System	
PRESET	
Datenausgang	
Stromversorgung	1,5V V357

Bestell-Nr. Order-No.	Messbereich Range mm	Genauigkeit Accuracy mm	Teller Disc mm	Ausladung Throat depth mm	Euro/St. Euro/Pc.
02027062	0 -10	0,04	ø 5,5	10	145,00

## Digitales Dicken-Messgerät, Ablesung 0,01 mm oder 0,0005"

565/2

Digital thickness gauge, reading 0.01 mm or 0.0005"



- Taster aus rostfreiem Stahl
- Bügel aus Gusseisen, lackiert
- Feder schließend
- Ablesung 0,01 mm oder 0,0005"
- im Etui

- rod and disc made of stainless steel
- frame made of case iron
- spring closed
- reading 0.01 mm or 0.0005"
- in case

ON / OFF	●
mm / inch (Unit)	●
HOLD-Funktion	
ABS-Funktion	
Absolut-System	
PRESET	
Datenausgang	
Stromversorgung	1,5V V357

Bestell-Nr. Order-No.	Messbereich Range mm	Ausladung Throat depth mm	Genauigkeit Accuracy mm	Euro/St. Euro/Pc.
02027064	0 - 12	19,7	0,02	140,00

## Messgerät mit digitaler Messuhr, Ablesung 0,01 mm oder 0,0005"

565/5

Digital thickness gauge with digital dial indicator



- mit Anlifthebel
- mit Digital-Messuhr  
Messbereich 10 mm,
- Ablesung 0,01 mm oder 0,0005"
- Taster aus rostfreiem Stahl
- Bügel aus Gusseisen, lackiert
- im Etui

- with lift mechanism
- with digital dial indicator  
range 10 mm
- reading 0.01 mm or 0.0005"
- rod and disc made of stainless steel
- frame made of cast iron
- in case

ON / OFF	●
mm / inch (Unit)	●
HOLD-Funktion	
ABS-Funktion	
Absolut-System	
PRESET	
Datenausgang	
Stromversorgung	1,5V V357

Bestell-Nr. Order-No.	Messbereich Range mm	Genauigkeit Accuracy mm	Teller Disc mm	Ausladung Throat depth mm	Euro/St. Euro/Pc.
02027071	0 -10	0,04	ø 10	30	140,00