

Wiha adapters.

For nut driver inserts and bits



7210 Tool shaft, style C 6.3.

Suitable for: DIN 3120, ISO 1174, style A 6.3 + A 10.
 Drive: DIN 3126, ISO 1173, style C 6.3.
 Application: For hand used nut driver sockets.

Order-No.				
01933	1/4	1/4	25	5
04204	3/8	1/4	30	5

For machine used nut driver sockets.



7230 Tool shaft, style A 5.5.

Standards: Adapter DIN 7428.
 Suitable for: DIN 3121, ISO 1174, style F 6.3.
 Drive: DIN 3126, ISO 1173, style A 5.5.
 Application: For machine used nut driver sockets.

Order-No.				
01934	1/4	5.5	50	5



7201 Connecting device with retaining ring, style G 6.3 + G 10 + G 12.5.

Suitable for: DIN 3126, ISO 1173, style D 6.3 and D 8.
 Drive: DIN 3121, ISO 1174, style G 6.3 + G 10 + G 12.5.
 Application: Suitable for bits C 6.3 and C 8.

Order-No.					
01924	1/4	1/4	25	D 6.3	2
01926	1/4	3/8	30	D 6.3	2
01922	1/4	1/2	35	D 6.3	2
01927	5/16	3/8	30	D 8	2
01923	5/16	1/2	35	D 8	2



7240 Tool shaft, style E 6.3.

Standards: Adapter DIN 7428.
 Suitable for: DIN 3121, ISO 1174, style F 6.3 and F 10.
 Drive: DIN 3126, ISO 1173, style E 6.3.
 Packaging: Plastic box, reusable and dust repellent.
 Application: For machine used nut driver sockets.
 Extra: Easily identifiable content with large symbols.

Order-No.				
04685	1/4	1/4	100	5
01935	1/4	1/4	50	5
04684	3/8	1/4	100	5
04362	3/8	1/4	50	5



NEW

7203 Connector, style G 12.5 with quick release chuck.

Sleeve: Steel, hardened.
 Suitable for: For bits according to DIN 3126, ISO 1173 style C 6.3.
 Drive: 1/2" internal square-drive in accordance with DIN 3126, ISO 1174, style G 12.5.
 Application: For use of C 6.3 bits.
 Extra: The alternative to G 12.5 bits.

Order-No.				
01930	1/4	1/2	50	2



7280 Tool shaft, style G 7.

Suitable for: DIN 3121, ISO 1174, style F 6.3.
 Drive: DIN 3126, ISO 1173, style G 7.
 Application: For machine used nut driver sockets.

Order-No.				
01936	1/4	7	75	5



24637 Power bit holder.

Material: High-quality chrome-molybdenum steel, through-hardened, chrome-plated and polished.
 Drive: DIN 3126.
 Application: For use of C 6.3 bits.

Order-No.				
33230	1/4	1/4	22	1

